



4002.17

Multisint EVO

SAE 10W/40

Lubricant for gasoline and Diesel engines, also turbocharged, of the latest generation.

PAKELO MULTISINT EVO SAE 10W/40 is a new generation lubricant fully formulated with Group II mineral base stocks and exclusive additives that confer to the product high detergent, dispersant, anti-oxidative, anti-corrosion, anti-wear and antifoam properties.

The bases used reduce product volatility, oxidation and formation of carbon residues.

This enables PAKELO MULTISINT EVO SAE 10W/40 to provide extraordinary anti-oxidative properties and to avoid formation of deposits also under high working temperatures.

The low volatility of synthetic bases results into a very significant reduction of oil losses caused by evaporation.

The SAE Viscosity Grade 10W/40 guarantees the correct viscosity for the most severe climatic conditions: this means easy and safe start-ups at very low temperatures (also at -25°C) and reduction of wear risks to minimum.

Thanks to the special viscosity properties, the use PAKELO MULTISINT EVO SAE 10W/40 can result into a prompt reply of the engine, making functioning soft and uniform.

PAKELO MULTISINT EVO SAE 10W/40 also exceeds the new Specification for gasoline engines API SN that includes engine tests that show better properties in terms of Fuel Economy compared to earlier generation products.

The product improves protection of all modern engines guaranteeing longer life of post-treatment devices used in modern cars or vans.

PAKELO MULTISINT EVO SAE 10W/40 exceeds the main performance levels on the market (Mercedes Benz, Volkswagen, etc.). It is possible to extend oil drain intervals, according to Constructors' recommendations.

Oil drain intervals are usually specified by OEMs and/or on-board electronic devices of latest generation vehicles; their recommendations should be taken into consideration to guarantee engine reliability.

PAKELO MULTISINT EVO SAE 10W/40 is perfectly compatible with all the lubricants that have the same application.

However, we recommend to avoid mixing it with other products for not undermining its exceptional properties.

4002.17

Multisint EVO

SAE 10W/40

Application fields

PAKELO MULTISINT EVO SAE 10W/40 has been developed for gasoline and Diesel engines, aspirated or supercharged (turbo), working also under heavy duty conditions as for instance “stop and go” service.

The product also satisfies the Specification ACEA A3/B4 and is thus particularly recommended for latest generation turbodiesel engines using “common rail” or “injection-pump” systems.

The use of special additives and highly selected mineral base stocks enable the use also in earlier generation of car engines and vans.

Performance levels

ACEA A3/B4, API SN / SM, MB 229.3, VW 502.00, VW 505.00, Renault RN0700.

Chemical-Physical Characteristics

Multisint EVO	Method analysis	Unit measure	Value SAE 10W/40
Density at 15°C	ASTM D1298	kg/l	0,867
Kinematic Viscosity at 40°C	ASTM D445	cSt	94,4
Kinematic Viscosity at 100°C	ASTM D445	cSt	14,5
Viscosity Index	ASTM D2270	-	160
C.C.S. Viscosity at -25°C	ASTM D5293	cP	6.900
HT-HS Viscosity at 150°C / 10 ⁶ s ⁻¹	ASTM D4683	cP	4,15
T.B.N. (Total Base Number)	ASTM D2896	mg(KOH)/g	10,8
Sulphated Ash	ASTM D874	% (w/w)	1,20
Flash Point (C.O.C.)	ASTM D92	°C	210
Pour Point	ASTM D97	°C	-33
Noack evaporability test	ASTM D5800	% (w/w)	11,2

The data just above refer to average values and must not be understood as guaranteed characteristics.

This Technical Data Sheet has been carefully checked to guarantee complete and precise information. However, we do not take any responsibility in case of damages caused by any mistakes or omissions. Due to continual product research and development, the information contained herein is subject to change without notification.